




XCC-E

Käft		XCC-22E	XCC-32E
Vikt, ex. Fäste (kg)	D-käft C-käft P-Käft S-käft	2050 2040 2210 1880	3001 3030 3130 2990
Längd, stängd käft (mm)	D-käft C-käft P-Käft S-käft	2276 2311 2327 2160	2565 2533 2563 2553
Bredd, öppen käft (mm)	D-käft C-käft P-Käft S-käft	1368 1438 1508 1083	1560 1684 1643 1332
Käftöppning, max (mm)	D-käft C-käft P-Käft S-käft	797 903 893 503	983 1119 1008 573
Klippkraft, spets (ton)	D-käft C-käft P-Käft S-käft	70 68 64 80	101 95 103 104
Öppning/stäng flöde (l/min) Öppning/stäng tryck, max (bar)		150~250 320	200~300 320
Rotation flöde (l/min) Rotation tryck, max (bar)		20~24 100	20~24 100
Bärmaskinens vikt (ton)		20~35	28~45
Klippförmåga med S-Käft			
 Solid rund järn, ytter dia. (mm)		35	45
 I-Balk, h x b x t (mm)		250 x 125 x 10	350 x 150 x 10
 H-Balk, h x b x t (mm)		200 x 200 x 10	250 x 250 x 14

